Technical specifications

VOIP HEADSET

HEADPHONE SECTION

- Speaker Dimension:ф40mm
- Impedance:32Ω
- Sensitivity:103dB S.P.L at 1KHz
- Frequency Response:20Hz-20,000Hz
- Rated Power:100mW
- Power Capability:1000mW
- Cable Length:Approx.2.5m
- Plug Type:ф3.5mmStero

MICROPHONE SECTION

- Microphone Unit:6*5mmDia.Electret condenser
- Microphone Directivity: Omni Direction
- Sensitivity:-58dB±3dB
- Impedance: Low
- Frequency Response:30Hz to 16,000Hz
- Standard Operating Voltage:3V

WEBCAM

- 100,000 Pixels CMOS image sensor
- Resolution: 640 x 480 mode up to 15F/s (VGA, software enhanced only)
- 320 x 240 (QVGA) mode up to 30 frames per second
- 352 x 288 (CIF) model up to 30 frames per second
- USB1.1, Hot plug and play
- 24-bit true color JPEG/BMP file format
- Automatic brightness adjustment and color compensation
- Fast snap button
- CD with auto installation driver
- Uninstall option
- Support Windows 98SE/2000/XP

Barcode specifications

CN-CP1 - 8717371843304

= 8pcs

CANYON

The Netherlands Taiwan United States Hong Kong

Pictures and specifications are subject to change without prior notice